

Sprint Airfluid XE Manual Powder Coating



Processable Materials

- Polyester powder coatings
- Acrylic powder coatings
 Fluoropolymer powder coatings
- Epoxy powder coatings
- Metallic powder coatings
 Practice powder coatings
 Special effect powder coatings

Technical Data	Sprint Airfluid XE
Input Voltage	85-250 V
Input Power	40 W
Input Frequency	50 - 60 Hz
Protection Class	IP 64
Air Inlet Pressure	0.6 - 0.8 Mpa, 6.0 - 8.0 bar, 87 - 116 PSI
Air Inlet Connection	G 1/4"
Exhaust Air Flow	0.05 - 20.0 Nm³/h
Operating Temperature	41.0 – 113.0 °F (5 – 45 °C)
Weight	83.8 lb (38.0 kg)

The new manual unit combines functionality and extraordinary design. By means of a central and dynamic knob, all parameters –grouped into four functional sections can be set easily. The unique Cascade characteristic line setting and the TRIBO compatibility offer a high level of flexibility for any powder. In combination with the new manual gun PEM-X1, the manual unit gives perfect coating results. The powder feeding is carried out directly from the original container – optionally out of the 60l stainless steel container.



Features

- Corona manual gun with an air-flushed high performance cascade
- Constant and reliable coating performance
- Closed loop air flow control (AFC) continuously measures and corrects air pressure and volume ensuring precise and optimal coating results
- Fully electronic control unit for reproducible results
- Optimal powder preparation for high quality requirements
- Clear and user-friendly operating interface for quickly and easily adjusting the coating parameters
- 50 coating recipes can be saved making it ideal for many color and object changes









Sprint Airfluid XE Manual Powder Coating



Sprint Airfluid XE - Box Feed		
Box Feed	Part Number	Description
Sprint XE Unit - Box Feed	2355402	Manual Unit Sprint Airfluid XE - Box Feed Version

Sprint Airfluid XE - Hopper Feed			
Hopper Feed	Part Number	Description	
Sprint XE Unit - Hopper Feed	2355404	Manual Unit Sprint Airfluid XE - Hopper Version	
Hoppers	Part Number	Description	
60L Hopper	264268	Sprint 60L Powder Tank	
25L Hopper	264224	Sprint 25L Powder Tank	
3L Hopper	HOP-0503	Sprint 3L Powder Tank	



(2355402)

Sprint XE Box Feed Included Items Corona manual gun PEM-X1

- Control device EPG-Sprint XE
- Injector PI-F1
- Suction lance with fluid cap
- Device cart with vibrating table
- Gun cable & powder hose length 16 ft (5m) Ø 7/16 in (Ø 11mm) Manual Sprint XE **Box Feed**
 - Power cord length 9.8 ft (3m)
 - Grounding cable 32.8 ft (10m)



Hopper Feed (2355404)

Hopper not included

Sprint XE Hopper Feed Included Items

- Corona manual gun PEM-X1 •
- Control device EPG-Sprint XE
- Injector PI-F1
- Device cart (optional with vibrating table)
- Gun cable & powder hose length 16 ft (5m) Ø 7/16 in (Ø 11mm)
- Power cord length 9.8 ft (3m)
- Grounding cable 32.8 ft (10m)
- Connection hose



Description	Part Number
PEM-X1 Spray Gun	2322587
PEM-X1 CG (Cup Gun Kit)	2356873
Flat Spray Nozzle X1	2321976
Wedge X1	2320488
Venturi Nozzle	241225
Electrode Holder X1 F	2322529
Round Spray Retrofit Package	2322493

Wagner Industrial Solutions

Powder Division 1770 Fernbrook Lane Plymouth, MN 55447 T 800.473.2524 F 630.503.2377

Liquid Division 337 South Arthur Ave Louisville, CO 80027 T 888.820.4498 F 303.438.5708





www.wagnersystemsinc.com





